




2 MP Fixed Dome IP-Camera 2.8~12mm Motor Varifocal ICR IR LED WDR H.265 GD-CI-AP2627V

- 2 Megapixel IP Camera with Full HD 1080P real time video
- Motorized Varifocal Lens: f = 2.8 - 12 mm
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 30m
- Audio Communication & Alarm Input / Output
- Ultra Low Light CMOS Sensor, Smart-IR Control



Specifications	GD-CI-AP2627V
Image Sensor:	1/2.8" Progressive Scan CMOS
Video Resolution:	1920 x 1080
Sensitivity Colour:	0.005 Lux @ F1.2
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/3 ~ 1/100, 000 sec
Slow Shutter:	Support
Lens Focal Length:	2.8 ~ 12 mm motorized vario focal lens
Horizontal Viewing Angle:	105° (Wide) ~ 35° (Tele)
Iris F-Number:	F1.4
Lens Mount:	Ø14
Mount:	Pan: 0° to 355°, tilt: 0° to 75°, rotation: 0° to 355°, 3-Axis Adjustment
Col/B&W:	On, Off, Auto, IR-cut filter removable (ICR)
Image settings:	Rotate mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
Wide Dynamic Range:	120 dB
Image Enhancement:	BLC, 3D DNR, HLC
Day/Night Switch:	Support auto, scheduled, day, night, triggered by alarm in
Max. IR Distance:	20, 30m (according to scene reflexion)
Wavelength:	850nm
Region of Interest:	1 fixed region for main stream and sub-stream
Video Compression:	Main Stream: H.265+, H.265, H.264+, H.264 Sub-Stream: H.265, H.264, MJPEG Third Stream: H.265, H.264
H.264 code profile:	Main Profile / High Profile
Triple Streams:	Supported while face detection, H.264+ and H.265+ are disabled
Frame Rate:	Main Stream: 50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720) 60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720) Sub Stream: 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240) Third Stream: 50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)
Bit Rate:	32Kbps ~ 16Mbps
Network Protocol:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, PPPoE, SNMP
Audio Compression:	G.726, G.711 a, u, MP2L2, PCM, G.722.1
Audio bit rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)
Environment Noise Filtering:	yes

Functions:	One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, Ip-address filter
SD memory:	Micro SD/SDHC/SDXC card with ANR (up to 128G), NAS (Support NFS, SMB/CIFS)
Event Source:	Video tampering, network disconnected, IP address conflicted, HDD full, HDD error, illegal login, motion detection
Network Interface:	1x 10, 100 Base T, TX PoE+ (RJ-45)
Video Outputs:	1 Test Monitor output (CVBS, 1 Vpp). Adapter cable with female BNC connector included.
Alarm Input/Output:	1 input, 1 output (up to 12 VDC, 30 mA)
Audio Input/Output:	1-ch audio input and 1-ch audio output
Intelligent Video Analytics:	Detection of intrusion, line crossing, unattended baggage, object removal and human faces. Video tampering detection such as defocus and change of the scene.
Line Crossing Detection:	Cross a pre-defined virtual line
Intrusion Detection:	Enter and loiter in a pre-defined virtual region
Unattended Baggage:	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
Object Removal:	Objects removed from the pre-defined region, such as the exhibits on display
Face Detection:	Human face appears in the image can be detected and trigger linkage method
Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP67, IK10
Standard:	ONVIF (Profile S, Profile G), CGI, ISAPI
Operating Temperature:	-30 °C ~ +60 °C (-22 °F ~ 140 °F)
Humidity:	less than 90%, non condensing
Supply Voltage:	12 VDC, PoE (IEEE 802.3af)
Power Consumption:	Max. 11 W
Dimensions:	Ø 153.4 × 133.1 mm (Ø 6.04 × 5.24 inch)
Weight:	1287 g (2.84 lb)

Accessories:

GD-BR-AMW01



GD-BR-AMP10



GD-BR-AMF06