



2 MP Mini Fixed Dome IP-Camera 2.8mm ICR IR LED dWDR H265 GD-CI-CC2616V

- Support Dual Power PoE/DC12V
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 30m
- Lens: f = 2.8 mm
- 2-Axis Adjustment
- H.265, H.264 & MJPEG compression modes
- 2 Megapixel IP Camera with Full HD 1080P real time video



Specifications	GD-CI-CC2616V
Image Sensor:	1/2.8" progressive Scan CMOS
Video Resolution:	1920 x 1080
Sensitivity Colour:	0.01 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/3 ~ 1/100, 000 sec
Slow Shutter:	Support
Lens Focal Length:	2.8 mm
Horizontal Viewing Angle:	114°
Iris F-Number:	F2.0
Lens Mount:	M12
Mount:	Pan: 0° to 355°, tilt: 0° to 75°, 2-Axis Adjustment
Col/B&W:	On, Off, Auto, IR-cut filter removable (ICR)
Wide Dynamic Range:	Digital WDR
Image Enhancement:	BLC, 3D DNR
Day/Night Switch:	Support auto, scheduled
Max. IR Distance:	Up to 30 m
Wavelength:	850nm
Region of Interest:	Support 1 fixed region
Image settings:	Saturation, brightness, contrast and sharpness adjustable through client software or web browser
Video Compression:	Main Stream: H.265+, H.265, H.264+, H.264 Sub-Stream: H.265, H.264, MJPEG
H.264 code profile:	Baseline Profile / Main Profile / High Profile
Bit Rate:	32Kbps ~ 8Mbps
Network Protocol:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
Frame Rate:	Main Stream 50Hz: 25fps (1920 x 1080, 1280 x 960, 1280 x 720) 60Hz: 30fps (1920 x 1080, 1280 x 960, 1280 x 720) Sub Stream 50Hz: 25fps (640 x 480, 640 x 360, 320 x 240) 60Hz: 30fps (640 x 480, 640 x 360, 320 x 240)
Event Source:	Video tampering, network disconnected, IP address conflicted
Functions:	Anti-flicker, mirror, password protection, privacy mask, watermark
Network Interface:	1x 10, 100 Base T, TX PoE (RJ-45)
Intrusion Detection:	Motion Detection
Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP67, IK10

Standard:	ONVIF (Profile S, Profile G), ISAPI
Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	less than 95%, non condensing
Supply Voltage:	12 VDC, PoE (IEEE 802.3af)
Power Consumption:	Max. 7 W
Dimensions:	Ø 111 × 82.4 mm (Ø 4.4 × 3.2 inch)
Weight:	400 g (0.88 lb)

Accessories:

GD-BR-AMW05



GD-BR-AMP09



GD-BR-AWJ02



GD-BR-AJX03



GD-BR-ASN01